

Forenta

Morristown, TN U.S.A.

"F" Series (Clear Buck) Legger-Utility

Models 472FGR/FGRH, 482FGR/FGRH and 472LSFG



Newly Designed . . .

- New fabricated frame with simple mechanics
- Dimple head and buck for strength
- Patented operating controls – close with either hand and lock with the other
- Clear buck design for easy operator dressing – can be used as a steam and vacuum board for finishing sweaters and hand ironing
- Variable pressure system for quality pressing



- Automatic cycle for pressing pant legs and manual cycle for utility pressing
- Two-hand control operation on hot head presses
- Insulated head design reduces heat loss and operator fatigue

Iron Attachment, Sleeve Board, Water Spray Optional.

Choice of three Head and Buck Shapes.

Specifications

Models 472/482FGR & 472LSFG

Electrical connections		472/482FGR 472LSFG	
Voltage 120V 1PH 50/60Hz .5amps		Standard	
Voltage 230V 1PH 50/60Hz .25amps		optional	
Optional Iron Attachment:			
Voltage 120V 1PH 50/60Hz		Wattage	1000
Approx. Consumption/hour		0.5 KWH	
Steam and Air connection			
Steam Inlet	NPT	1/2"	
Steam Outlet	NPT	1/2"	
Rec. steam pressure	PSIG	75-85	
	kPa	517-586	
Steam consumption @ 80psig(552 kPa)	lb/hr	51.8	
	kg/hr	23.5	
Compressed air	NPT	3/8"	
Air consumption	free air/cycle at 80psig	0.32 FT ³	
	free air/cycle at 552kPa	.009m ³	
Rec. air pressure	PSIG	80	
	kPa	552	
Air Vacuum Connection	NPT	1 1/4"	
Weight (crated)			
Shipping	472/482 FGR	lbs	720
		kg	327
	472 LSFG	lbs	800
		kg	363
1	Control Push Buttons	4	Steam Outlet connection
2	Steam connection	5	Air Vacuum Connection
3	Air connection	6	Electrical Connection

Detail Line Drawing (millimeters shown in parentheses)

